

HSL-Real-time Remote I/O Modules

PCI bus Master Controller

Master Card	PCI-7851	PCI-7852
Plug & Play	Yes	
Host I/F	PCI 2.1 Compliant	
Transfer Speed	6Mbps	
Max. Distance	200m/port	
Media I/F	RJ-45 x 2	RJ-45 x 4
HSL Ports	x 2	x 4
Memory	32KB	32KB x 2
Max. Slave Support	63	126

Robust Discrete I/O Module

Slave Modules N:NPN / P:PNP / R :Relay	Input N / P	Output N / P / R	No. of ID Address
HSL-DI32-M-N	32N	NA	2
HSL-DI32-M-P	32P	NA	2
HSL-DO32-M-N	NA	32N	2
HSL-DO32-M-P	NA	32P	2
HSL-DI16DO16-M-NN	16N	16N	1
HSL-DI16DO16-M-NP	16N	16P	1
HSL-DI16DO16-M-PN	16P	16N	1
HSL-DI16DO16-M-PP	16P	16P	1
HSL-R8DI16-M-N	16N	8R	1
HSL-R8DI16-M-P	16P	8R	1
Terminal Base Type	HSL-TB32-M-DIN		

Robust Analog I/O Module

Model V :Voltage / A :Current	Input Channels V / A	Output Channels V / A	No. of ID Address
HSL-AI16-M-V	16V	NA	1
HSL-AI16-M-A	16A	NA	1
HSL-AI16-M-T	16V/A	NA	2
Terminal Base Type	HSL-TB32-M-DIN		

Economic Single Slave Module

Slave Modules N:NPN / P:PNP / R :Relay	Input N / P	Output N / P / R	ID Address
HSL-DI16DO16-NN-DIN	16N	16N	1
HSL-DI16DO16-PN-DIN	16P	16N	1
Terminal Base Type	HSL-TB32-DIN		

Economic Dual Slave Module

Slave Modules N:NPN / P:PNP / R :Relay	Input N / P	Output N / P / R	No. of ID Address
HSL-DI32-X-DIN	32	No	2
HSL-DO32-X-DIN	No	32	2
Terminal Base Type	HSL-TB32U-DIN		

Economic Combined Slave Module

Slave Modules N:NPN / P:PNP	Input Channels	Output Channels	No. of ID Address
HSL-DI48DO16-XX-DIN	48	16	3
HSL-DI16DO48-XX-DIN	16	48	3
HSL-DI64-X-DIN	64	No	4
HSL-DO64-X-DIN	No	64	4
Terminal Base Type	HSL-TB64-DIN		

Compact I/O Module

Slave Modules N:NPN / P:PNP / R :Relay	Input channels N / P	Output channels N / P / R	No. of ID Address
HSL-DI8DO8-C-NN	8N	8N	1
HSL-DI8DO8-C-PN	8P	8N	1
HSL-DI8DO8-C-NP	8N	8P	1
HSL-DI8DO8-C-PP	8P	8P	1
Terminal Base Type	On-Board		